

We measure it.



# Infrared temperature measuring instrument

## testo 831 – Infrared thermometer for distance measurements



---

Non-contact measurement of surface temperature, ideally suitable for the food sector

---

2-point laser measurement point marker and 30:1 optics

---

Exact measurements even at greater distances

---

Large measuring range from -30 to +210 °C

---

Hold-function and display of min./max. values

---

Two adjustable alarm limit values

---

Also available as a set with the core thermometer testo 106

---

The testo 831 is an infrared thermometer for distance measurement. Thanks to its 30:1 optics, the measurement point diameter is only 3.6 cm at a distance of 1 m. This allows smaller objects such as yoghurt pots to be conveniently measured at a distance. Thanks to a 2-point laser marker, the diameter of the measurement point is displayed exactly, avoiding measurement errors. At two measurements per second, the testo 831 is so fast that scans of palettes or refrigerated shelving can be carried out.

### Set testo 831 and testo 106

For certain temperature measurements in the food sector, it is necessary to carry out an additional core temperature measurement. For this purpose, Testo offers an economic set consisting of the testo 831 and the proven core thermometer testo 106.

[www.testo.co.uk](http://www.testo.co.uk)

## Technical data / Accessories

### testo 831

testo 831, infrared thermometer including belt holder, battery, instruction manual and factory calibration certificate with the measurement points -20 and +80 °C



Part no. 0560 8310

### Set with testo 831 and testo 106

Set testo 831 and testo 106 - Infrared thermometer including belt holder, battery, instruction manual and factory calibration certificate with the measurement points -20 and +80 °C, and penetration thermometer testo 106 including TopSafe, belt holder, battery and instruction manual



Part no. 0563 8310

#### Sensor type Infrared

Meas. range	-30 to +210 °C
Accuracy ±1 digit	±1,5 °C or ±1,5% of mv (-20 to +210 °C ) ± 2 °C or ±2% of mv (remaining range )
Resolution	0,1 °C
Spectral range	8 to 14 μm

#### General technical data

Measurement rate	0,5 s
Distance to measurement spot	30:1
Emissivity	Adjustable 0.1 to 1.0
Oper. temp.	-20 to +50 °C
Storage temp.	-40 to +70 °C
Battery type	9V block battery
Battery life	15 h
Display	Illuminated LCD
Protection class	IP30
Dimensions	190 x 75 x 38 mm
Weight	200 g
Warranty	2 years

#### Accessories

#### Part no.

##### Accessories for measuring instrument

ISO calibration certificate/temperature, Infrared thermometers, calibration points -18°C, 0°C, +60°C	0520 0401	
ISO calibration certificate temperature, Infrared thermometers, calibration points 0°C, +60°C	0520 0452	
9V rech. battery for instrument, instead of battery	0515 0025	
Recharger for 9V rechargeable battery, for external recharging of 0515 0025 battery	0554 0025	